

Amendments in the Claims: (struck-through parts deleted and underlined parts added)

1. (currently amended) A baby stroller and safety restraint device comprising:

- 5 a panel having a front edge, a back edge, a pair of side edges, a top side, and a bottom side, said panel being generally arcuate so that said top side is generally concave from said front edge to said back edge, a pair of side walls being attached to said panel such that each is attached to one of said side edges and extends upwardly therefrom;
- 10 a strap assembly adapted for releasably securing a child against the top side of said panel being attached to said panel;
- a coupler being attached to said bottom side of said panel, said coupler being adapted for removably receiving a seatbelt;
- 15 a pair of wheels being rotatably coupled to and extending outwardly of said bottom side of said panel; ~~and~~
- a push handle being attached to said panel and being positioned adjacent to said back edge;
- a cover being snappily attached to said panel and extending from said front edge toward said back edge, said cover extending between said side walls; and
- 20 a carry handle consisting of a central member and a pair of legs being attached to and extending downwardly from said central member such that said carry handle is generally U-shaped, each of said legs having a bottom end, each of said bottom ends being rotatably coupled to one of said side walls, said bottom ends of said legs being generally centrally located between said
- 25 front and back edges, said central member being selectively positioned in a first position adjacent to said front edge or in a second position extending over and being spaced from said panel.

2. (original) The device according to claim 1, wherein said coupler

30 comprises at least one loop member positioned generally between said back and front edges.

BEST AVAILABLE COPY

3. (original) The device according to claim 1, wherein each of said wheels is positioned generally adjacent to one of said side edges, each of said wheels being positioned generally between said back and front edges.

5

4. (original) The device according to claim 1, wherein said push handle includes a pair of arms attached to and extending away from an elongated rod, each of said arms being selectively extendable into one of a pair of openings in said panel such that said rod may be selectively positioned in a retracted position adjacent to said panel or an extended position positioned away from said panel.

10

Claims 5-7 (cancelled)

8. (currently amended) The device according to claim 1, wherein said wheels extend less than three inches away from said back-side bottom side of said panel.

15

9. (currently amended) The device according to claim 1, further including: said coupler comprising at least one loop member positioned generally between said back and front edges;

20 each of said wheels being positioned generally adjacent to one of said side edges, each of said wheels being positioned generally between said back and front edges; and

said push handle including a pair of arms attached to and extending away from an elongated rod, each of said arms being selectively extendable into one of a pair of openings in said panel such that said rod may be selectively

25 positioned in a retracted position adjacent to said panel or an extended position positioned away from said panel;

~~a carry handle including a central member and a pair of legs being attached to and extending downwardly from said central member such that said carry~~

30 ~~handle is generally U-shaped, each of said legs having a bottom end, each of said bottom ends being rotatably coupled to one of said side walls, said~~

bottom ends of said legs being positioned generally between said front and
back edges; and
a cover being attached to said panel and extending from said front edge toward
said back edge, said cover extending between said side walls.

5

10. (currently amended) The device according to claim 9, wherein said wheels
extend less than three inches away from said ~~back side~~ bottom side of said panel.